

## Some Advantages

- Safe electric consumption
- Chemical consumption which is rate of 75
- Water consumption which is rate of 85. There is no way to explosion to any pan
- There is no way to diversity for all parts of the model
- In this system the human condition can not affect on a shape a type or a model of the pans because everything is done orderly
- Long life using
- You can memorize the process for getting the same solution while user selects
- This system is registered by ÇELIKHAN MACHINE



# S U S T A I N A B I L I T Y



### RESIN PROCESS

- This system works with 60 pieces of pants and it takes only 15 minutes with loading process and unloading. The average of resing mixture consumption for 60 regular typs of pans 2, 3 - 3, 5 liter.
- With this system you may get a standard type of solution for processing there is no an external effect such as users performance the rate of mixture time consuming and spray effect.
- This system is used with two nozzles and these nozzles connect with different angles through the resin to every area of the pants to get best solution.
- These systems treat chemicals through atomization on the pants without liquid and gas. It could be called a pulverized system of resin.
- In regular system you may need 10 persons for resin process who is loader, unloader and processor but in this system you only need 1 person for everything.

### HYP0 PROCESS

- This system works with 60 pieces of pants and it takes only 15 minutes with loading, process and unloading  
The average of hype mixture consumption for 60 regular types of pants 2, 5 - 35 liter.

### DYEING PROCESS

- This system works with 60 pieces of pants and it takes only 15 minutes with loading, process and unloading  
The average of hype mixture consumption for 60 regular types of pants 2, 5 - 35 liter.