

FELIVITAIN - PROFESSIONAL HORIZONTAL BRUSHING





| Technical Specifications | |
|------------------------------|-----------------------|
| Air regulation | 6 bar |
| Power consumption | 36w |
| Electrical regulation | 220 V, 240 vAC, 50 Hz |
| Production rate | 250 pcs. / 8h |
| 2 x Dung automatic filling | standard |
| 2 x Automatic dumping valve | standard |
| Electric socket outlet | standard |
| Lamp | standard |
| Panasonic PLC control system | standard |
| Height | 110 cm |
| Width x Length | 65x210 cm |
| Weight | 100 kg |





System Specifications And Advantages

- It is more different than regular brushing machines with is material quality and with it's new technics
- This machine is full filled with extra specifications by help us using PLC
- With it's contrivance it is easier to use and resist
- With help of the machine which having two buttons, you can achieve bottom support inflate operation automatically with one button and pushing to other one, you may adjust the down movement of button support and achieve the legs to turn automatically 180
- With the using of PLC and electronic card in it's system the machine does all the operations on it's own structure, it is enough for the operator only to press the buttons
- With its resistant construction it has the perfect upright posture, legs and body

SUSTAINABILTY






LEG ADJUSTMENT INSTRUCTIONS 1

Size enlargement minimum: 43 cm Size minimum: 22 cm Leg spraading dagres: 20

To enlarge or minimize the size the nuts behind the flanges which the legs are connected to needs to be loosened up this way you can slide legs to front or back on the slots.









LEG ADJUSTMENT INSTRUCTIONS 3

